

Non-Reactive Standard Adhesive

Milliken

ADHESIVE

For Carpet : Non-reactive adhesive for most applications (exception: extreme moisture)



NO LIMIT



NO LIMIT
New Construction



UP TO 95%
Renovations



DRY TIME
10-20 min



WORKING TIME
indefinite



4-Gallon Pail
Trowel / Roll-on

Non-Reactive Pressure Sensitive Adhesive

NEW CONSTRUCTION

For use with
RH up to:

No Limit

Installation
after new pour:

60 days

No testing required. No pH/RH limit.

RENOVATION

Above-grade
RH up to:

No Limit

On-grade, RH with
no vapor retarder:

95%

On-grade with vapor retarder: No limit.



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



1/16" x 1/32"
x 1/32"
U-Notch

FLOORING TYPE

Modular Carpet Tile

ESTIMATED COVERAGE
180-225 sf/gal



3/4" - 1"
Nap Paint
Roller

FLOORING TYPE

Modular Carpet Tile

ESTIMATED COVERAGE
Up to 350 sf/gal

WHAT'S SO SPECIAL ABOUT NON-REACTIVE?

- Milliken does not require the removal of old adhesives, significantly reducing floor prep cost and time.
- Non-reactive backing eliminates adhesive failures from plasticizer migration.
- No grinding, no solvents — simply knock down the high ridges of the existing adhesive and start installing immediately.

Non-Reactive Standard Adhesive



PRODUCT CHARACTERISTICS	Product Classification	Roll or trowel pressure sensitive adhesive
	Base Chemistry	Acrylic emulsion
	Appearance	Mint green to green tint as adhesive dries
	Consistency	Thin syrup
	Application	Trowel or roller
	Flammability	Non-flammable
	Freeze/Thaw	Protect from freezing
	Shelf Life	2 years (unopened)
MOISTURE	RH	New Construction - No Limit, No testing if installed 60 days after a new pour.
		Renovation (above-grade) - No Limit, No testing
		Renovation (on-grade with a confirmed vapor barrier) - No Limit
		Renovation (on-grade) - 95%
	pH	No limit
TIME/TRAFFIC	Open Time	Indefinite
	Dry Time	10-20 mins
	Working Time	Indefinite
	Traffic	Immediately
SUSTAINABILITY	Solvents	None
	Certifications	CRI Green Label Plus
	VOC (mg/m ³)	0.5 or less

STORAGE This product should be stored at temperatures between 40-100°F (4-38° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

