

Mosaic Moisture XT - Spray

Milliken

SPRAY ADHESIVE

For Mixed Media

Carpet Tile | 5 mm **FLEXFORM™** LVT



pH

NO LIMIT

RH

NO LIMIT



DRY TIME
10-20 min



WORKING TIME
4 hrs



LIGHT TRAFFIC / HEAVY TRAFFIC / HEAVY ROLLING LOADS
immediate use after floor is rolled within 1 hour of installation



22 oz Can
(6 per box)
Spray

Extreme Moisture Spray Adhesive

For use with RH up to **No RH Limit**

NO pH or RH limits.
NO TESTING REQUIRED.
NO VAPOR RETARDER REQUIRED.

Installation after new pour: **45 days** **CARPET ONLY 30 Days**



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



FLOORING TYPE

LVT/Modular Carpet Tile

ESTIMATED COVERAGE

125 sf/can

- Mosaic Moisture XT - Spray provides immediate shear strength following installation to allow instant access to finished flooring
- Instant shear strength also allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads
- Mosaic Moisture XT - Spray is a solvent-free, non-toxic product allowing occupation of spaces immediately following installation

Mosaic Moisture XT - Spray



PRODUCT CHARACTERISTICS	Product Classification	Extreme-moisture spray adhesive
	Base Chemistry	Water-based acrylic blend
	Appearance	Milky white frost bubbles
	Application	Spray
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C)
	Shelf Life	3 years (unopened)
MOISTURE	RH	No limit
	pH	No limit
TIME	Dry Time	10-20 mins until dry to touch
	Working Time	2 hrs (after tack)
TRAFFIC	Light Traffic	Immediately
	Heavy Traffic	Immediately
SUSTAINABILITY	Solvents	None
	VOC	0.0 g/ml calculated per EPA Test Method 8260B (exact measurement - 0.012g/100mL)
	Certifications	CRI Green Label Plus, Green Seal
	Propellant	non-ozone depleting HFC propellant

STORAGE This product should be stored at temperatures between 50-120°F (15-49° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

