

Mosaic 98 – Spray

Milliken

SPRAY ADHESIVE

For Mixed Media

Carpet Tile | 2.5 mm & 5 mm FLEXFORM™ LVT



pH

UP TO 11

RH

UP TO 98%



DRY TIME
10-20 min



WORKING TIME
4 hrs



LIGHT TRAFFIC / HEAVY TRAFFIC / HEAVY ROLLING LOADS
immediate use after floor is rolled within 1 hour of installation



22 oz Can
(6 per box)
Spray

Versatile Spray Adhesive for Mixed Media

For use with RH up to **98%**

Milliken is also the only manufacturer to offer adhesives with **NO pH or RH limits** and which **require NO testing**. Talk to your sales rep to learn more.

Installation after new pour: **45 days**



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



FLOORING TYPE

Carpet Tile /
2.5 mm & 5 mm
FLEXFORM™ LVT

ESTIMATED COVERAGE

150 - 185 sf/can

- Mosaic 98 - Spray provides immediate shear strength following installation to allow instant access to finished flooring
- Instant shear strength also allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads
- Mosaic 98 - Spray is a solvent-free, non-toxic product allowing occupation of spaces immediately following installation

Mosaic 98 – Spray

PRODUCT CHARACTERISTICS	Product Classification	High-moisture spray adhesive
	Base Chemistry	Water-based acrylic blend
	Appearance	Milky white frost bubbles
	Application	Spray
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C)
	Shelf Life	3 years (unopened)
MOISTURE	RH	98%
	pH	Up to 11
TIME	Dry Time	10-20 mins until dry to touch
	Working Time	2 hrs (after tack)
TRAFFIC	Light Traffic	Immediately
	Heavy Traffic	Immediately
SUSTAINABILITY	Solvents	None
	VOC	0.0 g/ml calculated per EPA Test Method 8260B (exact measurement - 0.012g/100mL)
	Certifications	CRI Green Label Plus, Green Seal
	Propellant	non-ozone depleting HFC propellant

STORAGE This product should be stored at temperatures between 50-120°F (15-49° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

Customer Concierge 800.824.2246 | millikenfloors.com
©2020 Milliken & Company | Design ©Milliken & Company | Made in the USA